


NOTES

1. ROAD BASECOURSE TO BE EXTENDED BENEATH AND 150 mm BEYOND THE FACE OF KERB AND GUTTER, APPROXS AND CROSSINGS.
2. CONCRETE TO BE OF 20 MPa COMPRESSIVE STRENGTH AT 28 DAYS FOR DISH CROSSINGS AND INTEGRAL KERB FOR CONCRETE ACCESSWAYS.
3. CONCRETE TO BE 15 MPa COMPRESSIVE STRENGTH AT 28 DAYS FOR KERB AND GUTTERING.
4. WHERE CONDUITS ARE REQUIRED TO BE PLACED PRIOR TO KERB CONSTRUCTION, KERB FACES SHALL BE MARKED FOR LOCATION WITH AN APPROVED TOOL OR AS DIRECTED BY THE SUPERINTENDING OFFICER.
5. ALL WORK IS TO BE APPROVED BY COUNCIL.
6. FORTY EIGHT (48) HOURS NOTICE IS TO BE GIVEN PRIOR TO THE PLACING OF CONCRETE TO ALLOW FOR INSPECTION BY COUNCIL'S OFFICER.

Fig. D5.Misc.9



SCALE 1:1 N.T.S.

SUBDIVISION CODE

CITY OF SHOALHAVEN
STANDARD KERB AND
GUTTER SHAPES
SHEET 1

ENGINEERING WORKS
MANAGER

DRAWN	C. FIESELER
CHECKED	J. BLOM
PLAN REF.	263709
DATE	04.MAY 1994