

Safe Work Instruction - Truck - Jet Patcher

DO NOT use this plant* unless you have been inducted in its safe use and operation by an Authorised Experienced Operator

This SWI may not cover all possible hazards and risks and should be referred to as a control measure in the risk assessment process. Additional training may be required for high risk plant. Site and task may change required PPE.

PERSONAL PROTECTIVE EQUIPMENT



Eye protection must be worn



Long and loose hair must be contained or covered.



Protective body clothing must be worn



Foot protection must be worn



Hand protection must be worn



High visibility clothing must be worn



P2 face mask must be worn when airborne dust or fumes are created

POTENTIAL HAZARDS AND RISKS

- Entanglement**
Entanglement in moving parts
- Electrical Shock or Burn**
Electrical shock or burn from plant contact with live electrical conductors
- Cutting, Stabbing or Puncturing**
Injury from unexpected movement of plant
- Other**
Injury due to plant malfunction or misuse
Injury from contact with moving parts
Injury due to operating of plant in unsuitable weather conditions
Skin irritation due to exposure to hazardous chemicals
Burn injury
- Slip, Trips, Falls**
Slip, trip, fall whilst entering and exiting vehicle
- Struck by Moving Object**
Struck by moving object due to unexpected movement of plant
- Exposure to High Pressure Fluid**
Injury from exposure to high pressure fluids

PRE-OPERATIONAL SAFETY CHECKS

- ✓ Complete site specific risk assessment
- ✓ Complete the appropriate pre-operational plant checklist
- ✓ Ensure you are familiar with plant operations and controls
- ✓ Ensure you have the appropriate SDS for kerosene and emulsion products
- ✓ Ensure that guards are fitted, secured and functional in accordance with manufacturers guidelines
- ✓ If traffic control is required, ensure to have the correct traffic control plans in place BEFORE commencement of work
- ✓ Seat belt to be worn

OPERATING PROCEDURES

- ✓ Keep clear of moving plant parts
- ✓ Operate plant to the conditions of the work area
- ✓ Always watch for bystanders when operating plant. Never assume a person is aware of your presence. Stop the machine if people step into the working area of the plant
- ✓ Driver to be alert when reversing plant

- ✓ Ensure that traffic control has been implemented in accordance with the traffic management plan
- ✓ Use 3 points of contact when entering and exiting plant
- ✓ All steps, ladders, platforms should be kept clean (to prevent slips & falls)
- ✓ Ensure you are aware of hazardous surface areas such as ditches and uneven and sloping terrain that may result in plant rollover
- ✓ Always be aware of wet/soft and loose edges
- ✓ Always be aware of your surroundings, keep a lookout for moving plant and vehicles
- ✓ Always operate within the prescribed safe working distances of overhead powerlines, use of a spotter if necessary
- ✓ Control rate of flow when filling so overflow can be prevented
- ✓ Lower the body of the truck immediately after tipping
- ✓ Before making adjustments bring plant to a complete standstill and isolate

ENDING OPERATIONS

- ✓ Allow plant to cool before performing any maintenance, refuelling or cleaning
- ✓ Ensure all cleaning procedures are carried out in close proximity to an EMERGENCY SHOWER
- ✓ Refuel plant at least 3 metres from combustibles
- ✓ Ensure plant is in good working order and stored in the appropriate location

DO NOT

- ✗ Do not use if plant is faulty. Attach a DO NOT OPERATE tag and report fault to your supervisor
- ✗ Do not overfill tanks
- ✗ Do not ride on back of truck
- ✗ Do not leave plant running unattended
- ✗ Do not place your hands in pinch points when handling chutes
- ✗ Do not stand on chutes to access the rear of the mixer apparatus
- ✗ Do not leave keys in machinery whilst unattended
- ✗ Do not wear loose jewellery
- ✗ Do not use mobile phone while operating plant

***Plant in this SWI refers to any machinery, equipment, appliance, container, implement and tool.**